

COLOURS

Circles

traditional rumbled circle kit paving blocks



DEPTH



60

Millimetres

FINISH

Rm

Rumbled



Radius:
1.55m



Diameter:
3.1m

Circles
colours

COLOURS



CASHEL



SLATE



Frost
Resistant



Pedestrian
Use



Light
Traffic



SPECIFICATION REFERENCE: NBS PLUS: Q24 110 SLAB/BRICK/SETT/COBBLE PAVINGS: 31, 315 BS EN: 1339:2003



T 028 8778 4208 | GB Sales T 0121 747 0202 | E specifications@ag.uk.com

AG.UK.COM

Circles

traditional rumbled circle kit paving blocks

DEPTH



60

Millimetres

FINISH

Rm

Rumbled





Radius:
1.55m



Diameter:
3.1m

Circles
Stock Information

STOCK INFORMATION

Standard Product Depth	Diameter (mm)	Radius (mm)	In Stock	Available Colours	m ² per pack	Units per pack	Weight per pack (t)	Packs per 8 wheeler	Packs per unit lorry
60mm	 3100	 1550	Yes	Cashel Rumbled / Slate Rumbled	7.56	1 Kit	1.05	17	26

SPECIFICATION REFERENCE: NBS PLUS: Q24 110 SLAB/BRICK/SETT/COBBLE PAVINGS: 31, 315 BS EN: 1339:2003



Frost Resistant



Pedestrian Use



Light Traffic





Circles

traditional rumbled circle kit paving blocks

DEPTH



60
Millimetres

FINISH



Radius: 1.55m
Diameter: 3.1m

STANDARDS + PERFORMANCE

Product Type	Traditional Rumbled Block Paving
Manufactured to	BS EN 1338:2003
Surface Layer	Durable, hard wearing with easy maintenance – > 350kg/m ³
Efflorescence	Reduced risk due to minimum 12 hour vapour curing
Bending Strength	3.6Mpa
Slip / Skid Risk	Extremely Low (>75 USRV)
Installed to	BS 7533-4:2006
NBS Plus	Q24 110

MANUFACTURING

Circle Kits are manufactured from specially sourced premium aggregates. Their unique colours are achieved by using the latest computerised mixing system to create a spectrum of colour blends. PLANT OF MANUFACTURE (POM): Made at our Toome production plant.

CERTIFICATION

ISO 14001	Environmental Management.
ISO 9001	Quality Management.
OSHAS 18001	Occupational Health and Safety Management.
CE Marking	Download our Declaration of Performance (DOP) data at: www.ag.uk.com/cemarking

EDGES

Circle Kits Supplied with a rumbled edge as standard.



Rumbled

FINISHES

Circle Kits are made with a colourfast, all-through mix of UV resistant pigments for vibrant, durable, lasting colours. It is rumbled with traditional methods to honour the authentic old cobble effect.



Frost Resistant



Pedestrian Use



Light Traffic

SPECIFICATION REFERENCE: NBS PLUS: Q24 110 SLAB/BRICK/SETT/COBBLE PAVINGS: 31, 315 BS EN: 1339:2003

SUSTAINABILITY

Energy Use	100% renewable
Water Used	90% rain water harvesting
Recyclable	100% of this product can be recycled
Manufacturing	Produced in the UK from locally sourced materials
Non-Primary materials	61 – 70% non primary
Waste Wood + Plastic:	100% recycled
Carbon Footprint	12.3 Kg CO ₂ / m ²
Carbon Reduction	20 Kg CO ₂ / m ²
BREEAM	'A' Rating – in accordance with the BRE Green Guide to Specification. (A+ Rating – when used with recycled sub-base).

