

TerraPave®


premium granite flagstones

DEPTHS


40-80
Millimetres

FINISHES


Tex
Textured

Gr
Ground


400 x 400mm




600 x 400mm




500 x 500mm

TerraPave®
colours + finishes


COLOURS + FINISHES




GENOA GROUND




GENOA TEXTURED



RIMINI GROUND




RIMINI TEXTURED




COMO GROUND




COMO TEXTURED




ARNO GROUND




ARNO TEXTURED



TUSCANY GROUND




TUSCANY TEXTURED




POLLENSA GROUND




POLLENSA TEXTURED



VERONA GROUND




VERONA TEXTURED



SORRENTO GROUND




SORRENTO TEXTURED



MILANO GROUND



MILANO TEXTURED



FLORENTO GROUND



FLORENTO TEXTURED

Frost
Resistant
Pedestrian
Use
Light
Traffic
Heavy
Traffic
Trolley
Friendly


TerraPave®

premium granite flagstones

DEPTHS



40-80
Millimetres


FINISHES



Textured




Ground



400 x 400mm



600 x 400mm



500 x 500mm

TerraPave®
technical information

STANDARDS + PERFORMANCE

Product Type	Granite Surfaced Flag Paving
Manufactured to	BS EN 1339:2003
Surface Layer	Durable, hard wearing with easy maintenance – min 380kg/m ³
Granite Content	Not less than 90% natural granite and quartz aggregate in surface layer
Efflorescence	Reduced risk due to minimum 12 hour vapour curing
Bending Strength	3.6Mpa up to 5.0Mpa – 3kN up to 5kN
Slip / Skid Risk	Extremely low to moderate (>75 USRV Textured), (>60 USRV Ground) Extremely low to moderate (>75 PTV Textured), (>40 PTV Ground)
Installed to	BS 7533-4:2006
NBS Plus	Q25 315

MANUFACTURING

TerraPave® flags are manufactured from specially selected granite and other natural aggregates. Their exceptional appearance is achieved by using the most up-to-date manufacturing and finishing equipment. Available in both a ground and textured finish. PLANT OF MANUFACTURE (POM): Made at our Toome production plant.


CERTIFICATION

ISO 14001	Environmental Management.
ISO 9001	Quality Management.
OSHAS 18001	Occupational Health and Safety Management.
CE Marking	Download our Declaration of Performance (DOP) data at: www.ag.uk.com/cemarking


EDGES

TerraPave® Ground Supplied with a straight chamfer edge as standard. A square edge is available on request.

TerraPave® Textured The edge is textured and has a slightly rounded appearance.



Square



Straight Chamfer



Frost Resistant



Pedestrian Use



Light Traffic



Heavy Traffic



Trolley Friendly

FINISHES


TerraPave® Ground is created using a unique diamond grinding process for a superior finish. TerraPave® Textured gives a higher level of slip resistance where required.

TerraPave® colour blends have been carefully developed using shades from natural granite aggregates. No dyes are used, so you can be confident that the colours you choose won't fade over time.

SPECIFICATION REFERENCE: NBS PLUS: Q25 SLAB/BRICK/SETT/COBBLE PAVINGS: 31, 315 **BS EN: 1339:2003**

SUSTAINABILITY

Energy Use	100% renewable
Water Used	90% rain water harvesting
Recyclable	100% of this product can be recycled
Manufacturing	Produced in the UK from locally sourced materials
Non-Primary materials	52 – 60% non primary
Waste Wood + Plastic:	100% recycled
Carbon Footprint	40mm: 15.8 Kg CO ₂ / m ² 50mm: 18.84 Kg CO ₂ / m ² 65mm: 24.50 Kg CO ₂ / m ² 70mm: 26.38 Kg CO ₂ / m ² 80mm: 30.15 Kg CO ₂ / m ²
Carbon Reduction	20 Kg CO ₂ / m ²
BREEAM	'A' Rating – in accordance with the BRE Green Guide to Specification. (A+ Rating – when used with recycled sub-base).



TerraPave®

premium granite flagstones

DEPTHS



40-80
Millimetres


FINISHES

Tex

Textured

Gr

Ground



TerraPave®
Stock Information

STOCK INFORMATION

Standard product depth	Size (mm)	In Stock	Available Colours (in both finishes)	m² per pack	Units per m²	Units per pack	Unit weight (kg)	Weight per pack (t)	Packs per 8 wheeler	Packs units per lorry
40mm	400 x 400	Yes	Rimini Ground / Verona Ground / Milano Ground	10.56	6.25	66	15.4	1.05	16	25
		MTO	Rimini Textured / Verona Textured / Milano Textured / Florento / Sorrento / Genoa / Pollensa / Arno / Como / Tuscany	19.2	6.25	120	15.4	1.85	9	15
	600 x 400	MTO	Rimini / Verona / Milano / Florento / Sorrento / Genoa / Pollensa / Arno / Como / Tuscany	19.2	4.16	80	23	1.84	9	15
	500 x 500	MTO	Rimini / Verona / Milano / Florento / Sorrento / Genoa / Pollensa / Arno / Como / Tuscany	19	4	76	24	1.824	9	15
50mm	400 x 400	Yes	Florento Ground / Florento Textured	8.64	6.25	54	19.2	1.05	16	25
		MTO	Rimini / Verona / Milano / Sorrento / Genoa / Pollensa / Arno / Como / Tuscany	15.36	6.25	96	19.2	1.843	9	15
	600 x 400	Yes	Rimini Ground / Verona Ground / Milano Ground / Florento Ground / Florento Textured	8.64	4.16	36	28.8	1.05	16	25
		MTO	Rimini Textured / Verona Textured / Milano Textured / Sorrento / Genoa / Pollensa / Arno / Como / Tuscany	15.36	4.16	64	28.8	1.843	9	15
	500 x 500	MTO	Rimini / Verona / Milano / Florento / Sorrento / Genoa / Pollensa / Arno / Como / Tuscany	15	4	60	30	1.8	9	15
65mm	400 x 400	MTO	Rimini / Verona / Milano / Florento / Sorrento / Genoa / Pollensa / Arno / Como / Tuscany	11.52	6.25	72	25	1.8	9	15
	600 x 400	MTO	Rimini / Verona / Milano / Florento / Sorrento / Genoa / Pollensa / Arno / Como / Tuscany	11.52	4.16	48	37.4	1.8	9	15
	500 x 500	MTO	Rimini / Verona / Milano / Florento / Sorrento / Genoa / Pollensa / Arno / Como / Tuscany	11	4	44	39	1.716	9	15
70mm	400 x 400	MTO	Rimini / Verona / Milano / Florento / Sorrento / Genoa / Pollensa / Arno / Como / Tuscany	10.56	6.25	66	26.9	1.775	9	15
	600 x 400	MTO	Rimini / Verona / Milano / Florento / Sorrento / Genoa / Pollensa / Arno / Como / Tuscany	10.56	4.16	44	40.3	1.773	9	15
	500 x 500	MTO	Rimini / Verona / Milano / Florento / Sorrento / Genoa / Pollensa / Arno / Como / Tuscany	11	4	44	42	1.848	9	15
80mm	400 x 400	MTO	Rimini / Verona / Milano / Florento / Sorrento / Genoa / Pollensa / Arno / Como / Tuscany	9.6	6.25	60	30.7	1.842	9	15
	600 x 400	MTO	Rimini / Verona / Milano / Florento / Sorrento / Genoa / Pollensa / Arno / Como / Tuscany	9.6	4.16	40	46.1	1.842	9	15
	500 x 500	MTO	Rimini / Verona / Milano / Florento / Sorrento / Genoa / Pollensa / Arno / Como / Tuscany	9	4	36	48	1.728	9	15



Frost Resistant



Pedestrian Use



Light Traffic



Heavy Traffic



Trolley Friendly

SPECIFICATION REFERENCE: NBS PLUS: Q25 SLAB/BRICK/SETT/COBBLE PAVINGS: 31, 315 BS EN: 1339:2003



T 028 8778 4208 | GB Sales T 0121 747 0202 | E specifications@ag.uk.com

AG.UK.COM